



河南红星矿山机械有限公司

HENAN HONGXING KUANGSHAN JIQI YOUXIAN GONGSI

Jaw Crusher

This series have many advantages, such as big reduction ratio, even granularity, simple structure, reliable working condition, convenient repair and economic operation, which are widely used for mine, smelting, building material, road, railway, irrigation works, chemical and materials with compression strength no more than 320 Mpa.





红 星

河南红星矿山机器有限公司

HENAN HONGXING KUANGSHAN JIQI YOUXIAN GONGSI



河南红星矿山机器有限公司





Jaw crusher technical parameters

Type	Feed Opening(mm)	Max. feeding size (mm)	Adjusting range of discharge opening (mm)	Capacity (t/h)	Rotation speed of eccentric shaft (r/min)	Motor power (kw)	Total Weight (t)	Dimensions (L*W*H)(mm)
PE-150×250	150×250	125	10-40	1-3	250	5.5	0.6	720×660×850
PE-200×300	200×300	180	15-50	2-6	260	7.5	1	910×750×990
PE-200×350	200×350	180	18-70	3-10	260	11	1.3	1000×870×990
PE-250×400	250×400	210	20-60	5-20	300	15	2.8	1300×1090×1270
PE-400×600	400×600	340	40-100	16-60	275	30	7	1730×1730×1630
PE-500×750	500×750	425	50-100	40-110	275	55	12	1980×2080×1870
PE-600×900 II	600×900	500	65-160	50-180	250	55-75	17	2190×2206×2300
PE-600×900	600×900	500	75-200	60-200	250	75	20	2290×2290×2400
PE-750×1060	750×1060	630	80-140	115-330	250	110	29	2660×2430×2800
PE-870×1060	870×1060	660	200-260	290-336	250	110	31.5	2810×2430×2800
PE-900×1060	900×1060	685	230-290	160-400	250	110	33	2870×2420×2940
PE-900×1200	900×1200	750	95-165	220-450	200	110	52	3380×2870×3330
PE-1000×1200	1000×1200	850	195-265	315-500	200	110	55	3480×3876×3330
PE-1200×1500	1200×1500	1020	150-300	400-800	180	160	100.9	4200×3300×3500
PEX-150×750	150×750	120	18-48	8-25	320	15	3.8	1200×1530×1060
PEX-250×750	250×750	210	25-60	13-35	330	30	5.5	1380×1750×1540
PEX-250×1000	250×1000	210	25-60	16-52	330	37	7	1560×1950×1390
PEX-250×1200	250×1200	210	25-60	20-61	330	45	8.5	2140×1660×1500
PEX-300×1300	300×1300	250	20-90	16-105	300	75	11	2720×1950×1600